

UNCLASSIFIED

CONFIDENTIAL
MASTER

DOC. NO. DCL 60-3-186

This material contains information affecting the
national defense of the United States within the
meaning of the Espionage Laws, Title 18, U.S.C.,
Sections 793 and 794, and the transmission or
revelation of its contents in any manner to an
unauthorized person is prohibited by law.

E. B. Nelson
DCL 60-3-186

THIS DOCUMENT CONSISTS
OF 6 PAGES NO. [REDACTED]

COPY 3A

M&PO
keep

M90033995

SUBSONIC CAPABILITY OF
PRATT AND WHITNEY
TURBOJET POWER PLANTS

H. E. Nicoll
AIRCRAFT APPLICATIONS UNIT

This document is
PUBLICLY RELEASABLE

Jerry E. Keyser
Authorizing Official
Date 3-5-78

March 23, 1960

DEPARTMENT OF ENERGY DECLASSIFICATION REVIEW	1st REVIEW DATE: 7-14-97
	2nd REVIEW DATE: 7-18-97
DETERMINATION (CIRCLE NUMBER(S))	1. CLASSIFICATION RETAINED
	2. CLASSIFICATION CHANGED TO
AUTHORITY: 10 AAC 1240C (U) ADD	3. CONTAINS NO DOE CLASSIFIED INFO
	4. COORDINATE WITH
NAME: <i>Jerry E. Keyser</i>	5. CLASSIFICATION CANCELED
	6. CLASSIFIED INFO BRACKETED
NAME: <i>Jed Davis</i>	7. OTHER (SPECIFY)

GENERAL  ELECTRIC

ATOMIC PRODUCTS DIVISION
AIRCRAFT NUCLEAR PROPULSION DEPARTMENT
Cincinnati 15, Ohio

This document contains Restricted Data as defined in Atomic Energy Act of 1954. Unauthorized disclosure is prohibited by Administrative and Criminal sanctions.

CLASSIFICATION CHANGED TO

DATE AUG 10 1961

H. F. Cancell

1
Chief, Declassification Branch

UNCLASSIFIED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

UNCLASSIFIED

PRELIMINARY REPORT

This report is preliminary and informal in nature and was prepared for use at the Aircraft Nuclear Propulsion Department, General Electric Company in the course of work under AEC contract AT(11-1)-174, U. S. Air Force contract AF33(038)-21102, or U. S. Air Force contract AF33(600)-38062. Views, opinions, conclusions or proposals expressed in the report are those of the author(s) only. This report is subject to revision upon further evaluation or availability of additional data.

LEGAL NOTICE

This report was prepared as an account of Government sponsored work. Neither the United States, nor the Commission, nor the Air Force, nor any person acting on behalf of the Commission or the Air Force:

- A. Makes any warranty or representation, express or implied, with respect to the accuracy, completeness, or usefulness of the information contained in this report, or that the use of any information, apparatus, method, or process disclosed in this report may not infringe privately owned rights; or
- B. Assumes any liabilities with respect to the use of, or for damages resulting from the use of any information, apparatus, method, or process disclosed in this report.

As used in the above "person acting on behalf of the Commission or Air Force" includes any employee or contractor of the Commission or Air Force to the extent that such employee or contractor prepares, handles, or distributes, or provides access to, any information pursuant to his employment or contract with the Commission or Air Force.

UNCLASSIFIED

THE UNIVERSITY OF CHICAGO

HC Leverett
 SC Levine
 FC Linn
 MH Long
 Document Control (1)

The major characteristics of three Pratt & Whitney power plant configurations are given in ADCL 60-3-18, "Summary of Pratt & Whitney Application Studies," by W. J. Tripp, Product Planning. Although the performance data presented is incomplete there is, none the less, sufficient information provided with which to perform preliminary application studies.

included in the tabulation of results are the weights, characteristics and performance of both penetrating and non-penetrating, three engine, F140 turbojet applications. These serve as a basis for comparison between the ANPD and Pratt & Whitney nuclear propulsion systems. It is to be noted that both F140 and nuclear J58 applications presented in Tables 1 and 2 are the results of an aircraft design optimization technique described in DC 59-11-93, "ANPD 704 Aircraft Computer Program No. 426, Combined Aircraft Program". Hence the aircraft presented are on a comparative basis.

All three Pratt & Whitney configurations involve two reactors which power either four or six nuclear J-58 turbojets. The four engine applications incorporate two PWAR-11 reactors at 200 MW each. For the six engine applications there are two reactor systems. One system incorporates two PWAR-11 reactors and the other involves two 300 MW reactors. The weights of these two reactor systems (including crew shield) differ by less than 2%. The difference in thrust output however at 10,000 sea level is appreciable with the PWAR-11 reactor associated with the lower value. Therefore, the six engine application with sea level penetration capability is powered by the two 300 MW system while the non-penetrating application incorporates the two PWAR-11 reactor system.

The weight breakdown, aircraft characteristics and performance for two non-penetrating applications are given in Table 1. The four engine, two PWAR-11, aircraft is designed for maximum cruise speed at 35,000 feet. The six engine application with the same reactor system is designed for maximum flight speed at 40,000 feet. This application also provides a flight speed of M 0.9 at 35,000 feet. The four engine application when designed for 40,000 feet exhibited a maximum flight Mach number less than M 0.8 and therefore was no longer investigated at that altitude.

Both PWAR-11 and 300 MW reactor systems provide a flight speed of M 0.80 at 40,000 feet for the six engine application. However, the PWAR-11 configuration is somewhat lighter and was therefore selected for the non-penetrating mission.

UNCLASSIFIED

~~SECRET~~
c4c
UNCLASSIFIED

Emergency cruise performance data (reactor out, 5,000 feet, AFHD) is not available for any of the Pratt & Whitney power plant configurations. However, previous experience with aircraft of comparable weight, design and $(L/D)_{\max}$ values, indicates that the emergency cruise requirement can be met. The excellent normal cruise capabilities associated with these applications are also indicative of adequate emergency performance.

The weight breakdown, aircraft characteristics and performance for the penetrating aircraft are given in Table 2. The four engine application is powered by two PWAR-11 reactors at 200 MW each, while the six engine application is powered by two 300 MW reactors. The aircraft are designed for maximum flight speed at sea level and although the gross weights differ appreciably the differences in thrust available have a compensating effect. As a result the sea level maximum flight speed of both applications is approximately M 0.9 to M 0.95. Because of these high subsonic flight speeds the aircraft characteristics are effected to the extent that the values of $(L/D)_{\max}$ associated with the penetrating aircraft are relatively low. As a result it appears doubtful that emergency cruise capability exists for either of these applications. However, no definite statement can be made in this regard until adequate performance data is available.

H. E. Nicoll

H. E. Nicoll
AIRCRAFT APPLICATIONS UNIT

HEN/elg

UNCLASSIFIED

~~SECRET~~

SECRET

-5-

UNCLASSIFIED

TABLE 1

WEIGHT SUMMARY, CHARACTERISTICS AND PERFORMANCE
OF NUCLEAR J-58 AND PL40 POWERED AIRCRAFT
NON-PENETRATING MISSION

	Four J-58 PWAR-11	Six J-58 PWAR-11	Three PL40 With Two J-75 Auxiliary Engines 426
Reactor Configuration			
Total Maximum Reactor Power - MW	400	400	
Weight Breakdown			
Wing	51,130	64,090	48,190
Fuselage	27,270	30,860	35,220
Empennage	9,737	13,200	11,950
Landing Gear	15,540	19,250	18,020
Propulsion System			
Nuclear Power Plant, Nacelles and Crew Shield	183,200	234,200	217,300
Auxiliary Power Plants			20,000
Equipment	<u>30,363</u>	<u>33,521</u>	<u>30,290</u>
Empty Weight	317,240	395,121	380,970
Fuel	37,650	56,500	40,000
Oil	3,200	4,000	2,400
Crew	900	900	900
Payload	<u>50,000</u>	<u>50,000</u>	<u>50,000</u>
Gross Weight	409,000	506,500	474,270
Aircraft Characteristics			
Wing Area - Sq Ft	4,000	4,900	4,600
Aspect Ratio	5.5	5.5	6.5
Thickness Ratio	0.075	0.075	0.09
Wing Sweep - .25c, Degrees	39	36	18
Performance			
(L/D) _{max} , With Payload	18.08	18.33	19.37
Ground Run, SL Std Day	6,600	5,000	5,000
Critical Field Length, SL Std Day	8,100	5,700	6,600
Maximum M_{cruise} and Corresponding Altitude	0.88 35,000 ft	.9 35,000 ft	0.8 32,500 ft

SECRET

UNCLASSIFIED

~~SECRET~~
UNCLASSIFIED

TABLE 2

WEIGHT SUMMARY, CHARACTERISTICS AND PERFORMANCE
OF NUCLEAR J-58 AND P140 POWERED AIRCRAFT
PENETRATING MISSION

	Four J-58 PWAR-11	Six J-58 300 MW	Three P140 With Two J-75 Auxiliary Power Plants
Reactor Configuration			426
Total Maximum Reactor Power - MW	400	400	
Weight Breakdown			
Wing	19,240	23,970	39,400
Fuselage	32,700	37,600	43,550
Empennage	6,387	8,172	9,070
Landing Gear	14,320	17,800	17,880
Propulsion System			
Nuclear Power Plant, Nacelles and Crew Shield	183,200	237,000	217,300
Auxiliary Power Plants			20,000
Equipment	29,521	32,473	30,000
Empty Weight	285,378	357,015	377,200
Fuel	37,650	56,500	40,000
Oil	3,200	4,000	2,400
Crew	900	900	900
Payload	50,000	50,000	50,000
Gross Weight	377,100	468,400	470,500
Aircraft Characteristics			
Wing Area - Sq Ft	2,800	3,300	3,800
Aspect Ratio	2.5	2.5	5.0
Thickness Ratio	0.06	0.06	0.09
Wing Sweep - .25c, Degrees	21	15	15
Performance			
(L/D) _{max} With Payload	11.50	11.66	16.5
Ground Run, SL Std Day	6,900	5,500	5,000
Critical Field Length, SL Std Day	8,600	6,400	6,600
Maximum Sea Level Mach Number	0.90-0.95	0.90-0.95	.83

UNCLASSIFIED

~~SECRET~~